

SAFETY DATA SHEET.

Issuing date 11-Nov-2015

Revision Date 26-Mar-2019

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 90125 BIG RED-RED GREASE

Recommended use of the chemical and restrictions on use

Product code F01417

Product Type Extremely Flammable Aerosol
Synonyms None

Supplier's details

Recommended Use Grease.
Uses advised against No information available

Manufactured For:
FPPF Chemical Company
117 West Tupper Street
Buffalo, NY 14201

Manufacturer
American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126
Phone:(734) 721-5930

Emergency telephone number
Chemical Emergency Phone Number

CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification


Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements
 Causes skin irritation.
 Causes serious eye irritation.
 May cause respiratory irritation. May cause drowsiness or dizziness.
 May be fatal if swallowed and enters airways.
 Extremely Flammable Aerosol
 Contains gas under pressure; may explode if heated



Appearance Opaque **Physical state** Aerosol **Odor** Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.
 Wear protective gloves, eye protection, face protection.
 Avoid breathing fumes, gas, mist, vapors, spray.
 Use only outdoors or in a well-ventilated area.
 Keep away from heat, sparks, open flames, hot surfaces - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

Specific treatment (see first aid on this label).
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice, attention
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice, attention.
 Take off contaminated clothing and wash it before reuse.
 IF INHALED : Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor, physician if you feel unwell.
 IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
 Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	30-40
HEPTANE	64742-49-0	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
ACETONE	67-64-1	10-20
BRIGHT STOCK, SEVERELY HYDROTR	64742-57-0	1-10
RED DYE	71819-51-7	<1
XYLENE	1330-20-7	<1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.
Protection of First-aiders	Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Hazardous Combustion Products Acrid smoke/fumes. Carbon oxides , Hydrocarbons, Fumes. Sulfur oxides.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level

3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HEPTANE 64742-49-0	TLV: 400 ppm STEL: 500 ppm	TWA: 500 ppm	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
ANTIMONY DIALKYL DITHIOCARBAMATE 15890-25-2	TWA: 0.5 mg/m ³ Sb	TWA: 0.5 mg/m ³ Sb (vacated) TWA: 0.5 mg/m ³ Sb	IDLH: 50 mg/m ³ Sb TWA: 0.5 mg/m ³ Sb
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	Not Established

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures

Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits. Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol		
Appearance	Opaque	Odor	Solvent
Color	Red	Odor Threshold	

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range		
Flash Point	-97 °C / -142 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	0.746	
Water solubility	No information available	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%) 48.49

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep away from children. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. oxidizing materials. Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation Respiratory irritation may occur if excessive exposure to product by inhalation.

Eye contact Causes serious eye irritation.

Skin contact	Causes skin irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
HEPTANE 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
ACETONE 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause respiratory irritation. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Irritating to eyes.
Sensitization Not a known sensitizer.
Germ cell mutagenicity Not a germ cell mutagen.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7	-	Group 3	-	-

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity This product does not contain any known or suspected reproductive hazards.
Specific target organ systemic toxicity (single exposure) May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ systemic toxicity (repeated exposure) No known effect based on information supplied.
Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects Skin, Eyes, Respiratory System, and Central Nervous System.
Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	6622 mg/kg
ATEmix (dermal)	8379 mg/kg
ATEmix (inhalation-vapor)	84 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
XYLENE 1330-20-7	-	13.4 mg/L LC50 Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static	-	3.82 mg/L EC50 water flea 48h 0.6 mg/L LC50 Gammarus lacustris 48h

Persistence and degradability

Bioaccumulation

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
ACETONE 67-64-1	-0.24
XYLENE 1330-20-7	3.15

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with local regulations. Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Pressurized container: Do not pierce or burn, even after use. Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD.QTY

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
NAPHTHENIC OIL, SEVERLY HYDROT	X	X	X	Not listed	X	X	X	X
HEPTANE	X	X	X	Not listed	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	x	X	X	X	X
ACETONE	X	X	X	X	X	X	X	X
BRIGHT STOCK, SEVERELY HYDROTR	X	X	X	Not listed	X	X	X	X
RED DYE	Not listed	Not listed	Not listed	Not listed	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- CHINA - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	<1	1.0

SARA 311/312 Hazard Categories

- Acute Health Hazard Yes
- Chronic Health Star Hazard Yes
- Fire Hazard Yes
- Sudden Release of Pressure Hazard Yes
- Reactive Hazard No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
ANTIMONY DIALKYL DITHIOCARBAMAT 15890-25-2	X		X
XYLENE 1330-20-7	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards -

HMIS Health Hazard 2* Flammability 4 Physical Hazard 1 Personal protection B

Chronic Hazard Star Legend *Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system damage*

Prepared By American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126

Issuing date 11-Nov-2015

Revision Date 26-Mar-2019

Revision Note
1 (M)SDS sections updated

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet